

Coast Guard, DOT

§ 91.40-3

required by § 91.27-1(a) of this subpart, the master must complete the applicable COI endorsement.

[USCG 1999-4976, 65 FR 6502, Feb. 9, 2000; 65 FR 11904, Mar. 7, 2000]

§ 91.27-15 Inspectors not limited.

(a) Nothing in this subpart shall be construed as limiting the inspector from making such tests or inspections as he deems necessary to be assured of the seaworthiness of the vessel.

Subpart 91.30—Inspection After Accident

§ 91.30-1 General or partial survey.

(a) A survey, either general or partial, according to the circumstances, shall be made every time an accident occurs or a defect is discovered which affects the safety of the vessel or the efficacy or completeness of its life-saving appliances, fire-fighting or other equipment, or whenever any important repairs or renewals are made. The survey shall be such as to insure that the necessary repairs or renewals have been effectively made, that the material and the workmanship of such repairs or renewals are in all respects satisfactory, and that the vessel complies in all respects with the regulations in this subchapter.

Subpart 91.35—Sanitary Inspections

§ 91.35-1 When made.

(a) An inspection of quarters, toilet and washing spaces, serving pantries, galleys, etc., shall be made at least once in every month. If the route of the vessel is such that it is away from a United States port for more than one month, an inspection shall be conducted at least once every trip.

Subpart 91.40—Drydocking

§ 91.40-1 Definitions relating to hull examinations.

As used in this part—

(a) *Drydock examination* means hauling out a vessel or placing a vessel in a drydock or slipway for an examination of all accessible parts of the vessel's underwater body and all through-hull fittings.

(b) *Internal structural examination* means an examination of the vessel while afloat or in drydock and consists of a complete examination of the vessel's main strength members, including the major internal framing, the hull plating, voids, and ballast tanks, but not including cargo or fuel oil tanks.

(c) *Cargo tank internal examination* means an examination of the vessel while afloat or in drydock and consists of an examination of the internals of all cargo tanks; except, if the vessel is certificated to carry cargoes regulated under part 38 or subchapter O of this chapter, the cargo tank internal examination must be accomplished as specified in parts 38 and 151 of this chapter respectively.

(d) *Underwater survey* means the examination, while the vessel is afloat, of all accessible parts of the vessel's underwater body and all through-hull fittings.

[CGD 84-024, 52 FR 39653, Oct. 23, 1987, as amended by CGD 84-024, 53 FR 32231, Aug. 24, 1988; CGD 95-028, 62 FR 51206, Sept. 30, 1997]

§ 91.40-3 Drydock examination, internal structural examination, cargo tank internal examination, and underwater survey intervals.

(a) Except as provided in paragraphs (b) through (g) of this section, each vessel must undergo drydock, internal structural, and cargo tank internal examinations as follows:

(1) Except under paragraph (a)(2) of this section, vessels that operate in salt water must be examined in accordance with the intervals set forth in Table 91.40-3(a) of this section. Where Table 91.40-3(a) indicates a 2.5 year examination interval, it means a vessel must undergo two examinations within any five year period. No more than three years may elapse between any two examinations.

TABLE 91.40-3(a)—SALT WATER SERVICE VESSELS EXAMINATION INTERVALS IN YEARS

	Single hull ship and barge	Double hull barge with internal framing ¹	Double hull barge with external framing ²	Single hull barge with independent tanks ³	Wood hull ship and barge	Unmanned deck cargo barge ⁴	Unmanned double hull freight barge ⁵
Drydock	2.5	5.0	5.0	5.0	2.5	5.0	5.0
Internal structural	2.5	2.5	2.5	2.5	2.5	2.5	2.5
Cargo tank internal	⁶ 2.5	⁶ 5.0	⁶ 10.0	⁶ 10.0	⁶ 2.5	⁶ 5.0

Note:

¹ Applicable to double hull tank barges (double sides, ends, and bottoms) when the structural framing is on the internal tank surface.

² Applicable to double hull tank barges (double sides, ends, and bottoms) when the structural framing is on the external tank surface accessible for examination from voids, double bottoms, and other similar spaces.

³ Applicable to single hull tank barges with independent cargo tanks which have a cargo containment envelope that is not a contiguous part of the hull structure and which has adequate clearance between the tanks and between the tanks and the vessel's hull to provide access for examination of all tank surfaces and the hull structure.

⁴ Applicable to unmanned/non-permissively manned deck cargo barge which carries cargo only above the weather deck and which provides complete access for examination of the inside of the hull structure.

⁵ Applicable to unmanned/non-permissively manned double hull freight barges (double sides, ends, and bottoms) the arrangement of which provides access for a complete internal structural examination as defined in § 91.40-1(b) without the necessity of entering cargo tanks or holds.

⁶ Or as specified in Part 151.

Coast Guard, DOT

§91.40-3

(2) Vessels that operate in fresh water at least six months in every 12 month period since the last drydock examination must be examined in accordance with the intervals set forth in Table 91.40-3(b) of this section. Where

Table 91.40-3(b) indicates a 2.5 year examination interval, it means a vessel must undergo two examinations within any five year period. No more than three years may elapse between any two examinations.

TABLE 91.40-3(b)—FRESH WATER SERVICE VESSELS EXAMINATION INTERVALS IN YEARS

	Single hull ship and barge	Double hull barge with internal framing ¹	Double hull barge with external framing ²	Single hull barge with independent tanks ³	Wood hull ship and barge	Unmanned deck cargo barge ⁴	Unmanned double hull freight barge ⁵
Drydock	5.0	10.0	10.0	10.0	2.5	10.0	10.0
Internal structural	5.0	5.0	5.0	5.0	2.5	5.0	5.0
Cargo tank internal	⁶ 5.0	⁶ 5.0	⁶ 10.0	⁶ 10.0	⁶ 2.5	⁶ 5.0

Note:

¹ Applicable to double hull tank barges (double sides, ends, and bottoms) when the structural framing is on the internal tank surface.

² Applicable to double hull tank barges (double sides, ends, and bottoms) when the structural framing is on the external tank surface accessible for examination from voids, double bottoms, and other similar spaces.

³ Applicable to single hull tank barges with independent cargo tanks which have a cargo containment envelope that is not a contiguous part of the hull structure and which has adequate clearance between the tanks and between the tanks and the vessel's hull to provide access for examination of all tank surfaces and the hull structure.

⁴ Applicable to unmanned/non-permissively manned deck cargo barge which carries cargo only above the weather deck and which provides complete access for examination of the inside of the hull structure.

⁵ Applicable to unmanned/non-permissively manned double hull freight barges (double sides, ends, and bottoms) the arrangement of which provides access for a complete internal structural examination as defined in § 91.40-1(b) without the necessity of entering cargo tanks or holds.

⁶ Or as specified in Part 151.

Coast Guard, DOT

§91.40-5

(b) During each inspection or reinspection for certification, all wing voids, rakes, cofferdams, and other void spaces on barges must be opened and checked from on-deck for the presence of water or cargo indicating hull damage or cargo tank leakage. If water or cargo is not present, these spaces need not be gas freed, ventilated, cleaned, or otherwise prepared for personnel entry. If water or cargo is present, an internal structural examination may be required.

(c) If, during an internal structural, cargo tank internal examination, or underwater survey, damage or deterioration to the hull plating, structural members, or cargo tanks is discovered, the Officer in Charge, Marine Inspection, may require the vessel to be drydocked or otherwise taken out of service to further assess the extent of the damage and to effect permanent repairs.

(d) Vessels less than 15 years of age (except wooden hull vessels) that are in salt water service with a 2.5 year drydock interval (as indicated in Table 91.40-3(a) of this section) or that are in fresh water service with a five year drydock interval (as indicated in Table 91.40-3(b) of this section) may be considered for an underwater survey instead of alternate drydock examinations, provided the vessel is fitted with an effective hull protection system. Vessel owners or operators must apply to the Officer in Charge, Marine Inspection, for approval of underwater surveys instead of alternate drydock examinations for each vessel. The application must include the following information:

(1) The procedure to be followed in carrying out the underwater survey.

(2) The location where the underwater survey will be accomplished.

(3) The method to be used to accurately determine the diver location relative to the hull.

(4) The means that will be provided for examining through-hull fittings.

(5) The means that will be provided for taking shaft bearing clearances.

(6) The condition of the vessel, including the anticipated draft of the vessel at the time of the survey.

(7) A description of the hull protection system.

(e) Vessels otherwise qualifying under paragraph (d) of this section, that are 15 years of age or older, may be considered for continued participation in or entry into the underwater survey program on a case-by-case basis if—

(1) Before the vessel's next scheduled drydocking, the owner or operator submits a request for participation or continued participation to Commandant (G-MOC);

(2) During the vessel's next drydocking after the request is submitted, no appreciable hull deterioration is indicated as a result of a complete set of hull gaugings; and

(3) The results of the hull gauging and the results of the Coast Guard drydock examination together with the recommendation of the Officer in Charge, Marine Inspection, are submitted to Commandant (G-MOC) for final approval.

(f) Each vessel which has not met with the applicable examination schedules in paragraphs (a) through (e) of this section because it is on a voyage, must undergo the required examinations upon completion of the voyage.

(g) The Commandant (G-MOC) may authorize extensions to the examination intervals specified in paragraph (a) of this section.

[CGD 84-024, 52 FR 39653, Oct. 23, 1987, as amended by CGD 84-024, 53 FR 32231, Aug. 24, 1988; CGD 84-024, 53 FR 34872, Sept. 8, 1988; CGD 95-072, 60 FR 50464, Sept. 29, 1995; CGD 96-041, 61 FR 50729, Sept. 27, 1996; CGD 95-028, 62 FR 51206, Sept. 30, 1997]

§91.40-5 Notice and plans required.

(a) The master, owner, operator, or agent of the vessel shall notify the Officer in Charge, Marine Inspection, whenever the vessel is to be drydocked regardless of the reason for drydocking.

(b) Each vessel, except barges, that holds a Load Line Certificate must have on board a plan showing the vessel's scantlings. This plan must be made available to the Coast Guard marine inspector whenever the vessel undergoes a drydock examination, internal structural examination, cargo tank internal examination, or underwater survey or whenever repairs are made to the vessel's hull.